



Corporate Offices
 19855 SW 124 Ave.
 Tualatin, Or 97062
 Phone: (503) 692-3322
 www.lumberproducts.com

Branches

Tualatin, OR (503) 692-3322	Las Vegas, NV (702) 795-8866	Chandler, AZ (520) 796-9663
Spokane, WA (509) 928-8200	Salt Lake City, UT (801) 972-9393	Albuquerque, NM (505) 924-2270
Bozeman, MT (406) 522-0435	Kent, WA (425) 251-5151	Denver, CO (303) 375-1500
Eugene, OR (541) 687-0411	Boise, ID (208) 336-3911	

One Year Limited Warranty

LUMBER PRODUCTS (LP) warrants that each stile and rail door from the Ultimate Wood Door Collection (UWDC) is a product made of suitable material and workmanship. Furthermore, we warrant that each door is free from defects that would render such door unserviceable for its intended purpose. All UWDC doors by LP are warranted to retain form and function during normal use, providing proper handling and finishing instructions are followed.

ONE (1) Year Limited Warranty

The limit of LP's warranty is that each UWDC manufactured door will be repaired or replaced if a structural instability is found and it is determined that the defect was caused during the manufacturing process. Each UWDC manufactured door will be repaired or replaced if warping or twisting occurs. Warp on the plane of the door itself will be considered a defect only if it exceeds 1/4" when measured as a deviation from a straight edge. Wood naturally swells and shrinks due to climate and location. LP retains the right to delay replacement decisions until such time that proper acclimatization may occur.

Exclusions (This warranty excludes the following:)

- ◆ Oversized Doors:
Doors wider than 3'0" or Doors taller than 8'0"
- ◆ Shrinking or Swelling
- ◆ Doors altered by anyone other than LP
- ◆ Natural Variations in Color and Texture of Wood
- ◆ Buyer's Neglect
- ◆ Improper Finish or Seal of the Door
- ◆ Improper Hanging
- ◆ Improper Handling
- ◆ Any door improperly prepared, installed coated or used in an inappropriate manner or application

Handling & Finishing Instructions

All doors must be handled carefully and stored flat on a level surface in a dry, well ventilated building. Doors should not be subject to extremes of heat, dryness, or humidity. Doors should be conditioned to average prevailing relative humidity before installation.

Doors should be delivered to a building site only after plaster, texture or cement is completely dry, and if it is to be stored at building site for longer than one week, the entire door should be sealed with a penetrating base sealer or the equivalent.

Before finishing, the door surface must be clean, dry, and acclimatized. To prevent moisture penetration the entire door including all six (6) sides must receive at least two coats of paint, varnish, or sealer immediately after all machining and fitting.

Finish must be applied precisely in accordance with the manufacturer's instruction. Water-thinned paint should be used only after application of an oil base primer.



THE
Ultimate
 WOOD DOOR
 COLLECTION

Knotty Alder Series

Exclusively from Lumber Products





Interior Doors

Interior Knotty Alder Doors from the Ultimate Wood Door Collection combine the warmth of the real wood with rustic beauty and engineered durability. Available in a wide range of styles and sizes, this collection is certain to offer an option to suit your home and lifestyle!

Warm

Rustic

Durable

Unique

Personal

Beautiful

Exterior Doors

Your home's entry creates a first impression... and a Knotty Alder Entry Door from the Ultimate Wood Door Collection makes that first impression personal, unique, and beautiful. It is the perfect complement to your interior Knotty Alder series doors!



2 Panel Arch Top

KA82A - 6/8
1-3/8" x 1/6, 1/8, 1/10, 2/0, 2/2, 2/4, 2/6, 2/8, 2/10, 3/0

KA82A - 8/0
1-3/8" x 1/6, 2/0, 2/4, 2/6, 2/8, 3/0

KA82A Bifold - 6/8
1-3/8" x 2/0, 2/6, 3/0



2 Panel Arch Top Plank

KA82AP - 6/8
1-3/8" x 1/6, 1/8, 1/10, 2/0, 2/2, 2/4, 2/6, 2/8, 2/10, 3/0

KA82AP - 8/0
1-3/8" x 1/6, 2/0, 2/4, 2/6, 2/8, 3/0

KA82AP Bifold - 6/8
1-3/8" x 2/0, 2/6, 3/0



2 Panel Square Top

KA82S - 6/8
1-3/8" x 1/6, 1/8, 2/0, 2/4, 2/6, 2/8, 3/0

KA82S - 8/0
1-3/8" x 2/0, 2/4, 2/6, 2/8, 3/0

KA82S Bifold - 6/8
1-3/8" x 2/0, 2/6, 3/0



2 Panel Square Top Plank

KA82SP - 6/8
1-3/8" x 1/6, 1/8, 2/0, 2/4, 2/6, 2/8, 3/0

KA82SP - 8/0
1-3/8" x 2/0, 2/4, 2/6, 2/8, 3/0

KA82SP Bifold - 6/8
1-3/8" x 2/0, 2/6, 3/0



3 Flat Panel Shaker

KA760 - 6/8
1-3/8" x 1/6, 1/8, 2/0, 2/4, 2/6, 2/8, 3/0

KA760 Bifold - 6/8
1-3/8" x 2/0, 2/6, 3/0



Pantry Door

Pantry - 6/8
1-3/8" x 2/0, 2/4, 2/6, 2/8, 3/0

Pantry - 8/0
1-3/8" x 2/4, 2/6



1-Lite French Door

1501 - 6/8
1-3/8" x 1/6, 1/8, 2/0, 2/2, 2/4, 2/6, 2/8, 3/0

1501 - 8/0
1-3/8" x 2/0, 2/4, 2/6, 2/8, 3/0



10-Lite French Door

1510 - 6/8
1-3/8" x 2/0, 2/6, 3/0

1512 - 8/0 12-Lite
1-3/8" x 2/6, 3/0

Features

Double Hip Raised Panels

- 3/4" on Interior Collection
- 1-1/4" on Exterior Collection

Select Grade, Color Matched Veneers for Consistent Appearance

Extra Thick Veneers to Add Durability

Solid Edge Strips to Enhance Stability

Dual Quality Control to Ensure Superior Appearance and Performance

Door Specifications

Top Rail	4-1/8"
Lock Rail	6-7/8"
Bottom Rail: Passage	8-25/32"
Interior Stile Width	4-1/8"
Exterior Stile Width	5-1/8"
Bottom Rail: Bifold	7-1/2"
Stiles: Bifolds	1-3/4"
Panels:	Double Hip Raised



1 Raised Panel Square Top Plank

KA1SP - 6/8
1-3/4" x 3/0

KA1SP - 8/0
1-3/4" x 3/0, 3/6



2 Raised Panel Arch Top

KA82A - 6/8
1-3/4" x 1/6, 2/0, 2/4, 2/6, 2/8, 3/0, 3/6

KA82A - 8/0
1-3/4" x 1/6, 2/0, 2/4, 2/6, 2/8, 3/0, 3/6



2 Raised Panel Arch Top Plank

KA82AP - 6/8
1-3/4" x 2/0, 2/4, 2/6, 2/8, 3/0, 3/6

KA82AP - 8/0
1-3/4" x 2/0, 2/4, 2/6, 2/8, 3/0, 3/6



2 Raised Panel Square Top

KA82S - 6/8
1-3/4" x 1/6, 2/0, 2/4, 2/6, 2/8, 3/0, 3/6

KA82S - 8/0
1-3/4" x 1/6, 2/0, 2/4, 2/6, 2/8, 3/0, 3/6



2 Raised Panel Square Top Plank

KA82SP - 6/8
1-3/4" x 1/6, 2/0, 2/4, 2/6, 2/8, 3/0, 3/6

KA82SP - 8/0
1-3/4" x 1/6, 2/0, 2/4, 2/6, 2/8, 3/0, 3/6



1 Lite

KA7002 - 6/8
1-3/4" x 2/6, 2/8, 3/0

KA7002 - 8/0
1-3/4" x 2/6, 2/8, 3/0



Craftsman 2 Panel 6-Lite with Dentil Shelf

KA2206 - 6/8
1-3/4" x 3/0

KA2206 1 Panel 1-Lite Sidelite
1-3/4" x 1/2

Available with 1-Panel 1-Lite Sidelite

*Ask us about availability of 20 minute fire rated doors