



**Corporate Offices**  
19855 SW 124th Ave.  
Tualatin, Or 97062  
phone: (503) 692-3322  
www.lumberproducts.com

**Branches**

Tualatin, OR Branch (503) 692-3322	Eugene, OR Branch (541) 687-0411	Kent, WA Branch (425) 251-5151	Denver, CO Branch (303) 375-1500
Door Division Tualatin, OR (503) 612-1818	Medford, OR Branch (541) 773-3696	Boise, ID Branch (208) 336-3911	Sacramento, CA Branch (916) 388-5888
Spokane, WA Branch (509) 928-8200	Las Vegas, NV Branch (702) 795-8866	Chandler, AZ Branch (520) 796-9663	
Bozeman, MT Branch (406) 522-0435	Salt Lake City, UT Branch (801) 972-9393	Albuquerque, NM Branch (505) 924-2270	

## One Year Limited Warranty

LUMBER PRODUCTS (LP) warrants that each stile and rail door from the Ultimate Wood Door Collection (UWDC) is a product made of suitable material and workmanship. Furthermore, we warrant that each door is free from defects that would render such door unserviceable for its intended purpose. All UWDC doors by LP are warranted to retain form and function during normal use, providing proper handling and finishing instructions are followed.

**One (1) Year Limited Warranty**

The limit of LP's warranty is that each UWDC manufactured door will be repaired or replaced if a structural instability is found and it is determined that the defect was caused during the manufacturing process. Each UWDC manufactured door will be repaired or replaced if warping or twisting occurs. Warp on the plane of the door itself will be considered a defect only if it exceeds 1/4" when measured as a deviation from a straight edge. Wood naturally swells and shrinks due to climate and location. LP retains the right to delay replacement decisions until such time that proper acclimatization may occur.

**Exclusions** (This warranty excludes the following:)

- ◆ Oversize Doors:  
Doors wider than 3'0" or Doors taller than 8'0"
- ◆ Shrinking or Swelling
- ◆ Doors altered by anyone other than LP
- ◆ Natural Variations in Color and Texture of Wood
- ◆ Buyer's Neglect
- ◆ Improper Finish or Seal of the Door
- ◆ Improper Hanging
- ◆ Improper Handling
- ◆ Any door improperly prepared, installed, coated or used in an inappropriate manner or application

## Handling & Finishing Instructions

All doors must be handled carefully and stored flat on a level surface in a dry, well ventilated building. Doors should not be subjected to extremes of heat, dryness, or humidity. Doors should be conditioned to average prevailing relative humidity before installation.

Doors should be delivered to a building site only after plaster, texture or cement is completely dry, and if it is to be stored at building site for longer than one week, the entire door should be sealed with a penetrating base sealer or the equivalent.

Before finishing, the door surface must be clean, dry, and acclimatized. To prevent moisture penetration the entire door including all six (6) sides must receive at least two coats of paint, varnish, or sealer immediately after all machining and fitting.

Finish must be applied precisely in accordance with the manufacturer's instruction. Water-thinned paint should be used only after application of an oil base primer.



THE  
*Ultimate*  
WOOD DOOR  
COLLECTION

PINE SERIES

*Exclusively from LP*

The Ultimate Wood Door Collection combines the warm hues and natural beauty of real wood with the performance of a quality engineered product. With a wide variety of sizes, styles, and species, the Ultimate Wood Door Collection has the right door to enhance your interior design, and the durability to grace your home for years to come.

**Features**

- ◆ Panel doors feature 3/4" thick double-hip split proof raised panels to provide high performance, aesthetic appeal, and traditional architectural designs
- ◆ E1 Glue to ensure low formaldehyde content (1-part/million)
- ◆ All veneers are select grade and color matched for a consistent appearance
- ◆ Pine louvered door slats are thicker than industry standard to prevent warping & shaking
- ◆ Extra veneer thickness on all doors provides added durability
- ◆ Dual quality control inspection
- ◆ 1-year warranty

# Knotty Pine



KP82

**2-Panel Sq Top 6/8**  
2/0, 2/2, 2/4, 2/6, 2/8, 2/10, 3/0

**2-Panel Sq Top 8/0**  
1/6, 2/0, 2/4, 2/6, 2/8, 3/0

**2-Panel Sq Top Bifold 6/7**  
2/0, 2/6, 3/0



KP82P

**2-Panel Sq Top Planked 6/8**  
1/6, 1/8, 1/10, 2/0, 2/2, 2/4, 2/6, 2/8, 2/10, 3/0

**2-Panel Sq Top Planked 8/0**  
1/6, 2/0, 2/4, 2/6, 2/8, 3/0

**2-Panel Sq Top Planked Bifold 6/7**  
2/0, 2/6, 3/0



KP82A

**2-Panel Arch Top 6/8**  
1/6, 1/8, 1/10, 2/0, 2/2, 2/4, 2/6, 2/8, 2/10, 3/0

**2-Panel Arch Top 8/0**  
1/6, 2/0, 2/4, 2/6, 2/8, 3/0

**2-Panel Arch Top Bifold 6/7**  
2/0, 2/6, 3/0



KP82AP

**2-Panel Arch Top Planked 6/8**  
1/6, 1/8, 1/10, 2/0, 2/2, 2/4, 2/6, 2/8, 2/10, 3/0

**2-Panel Arch Top Bifold 6/7**  
2/0, 2/6, 3/0

# Clear Pine



CP82A

**2-Panel Arch Top 6/8**  
1/6, 1/8, 1/10, 2/0, 2/2, 2/4, 2/6, 2/8, 2/10, 3/0

**2-Panel Arch Top 8/0**  
1/6, 2/0, 2/4, 2/6, 2/8, 3/0

**2-Panel Arch Top Bifold 6/7**  
2/0, 2/6, 3/0



CP44 Radiata

**4-Panel 6/8**  
1/4, 1/6, 1/8, 1/10, 2/0, 2/2, 2/4, 2/6, 2/8, 2/10, 3/0

**4-Panel Bifold 6/7**  
2/0, 2/6, 3/0



CP66 Radiata

**6-Panel 6/8**  
1/4, 1/6, 1/8, 1/10, 2/0, 2/2, 2/4, 2/6, 2/8, 2/10, 3/0

**6-Panel Bifold 6/7**  
2/0, 2/6, 3/0



730 Full Louver

**Full Louver 6/8**  
1/6, 1/8, 2/0, 2/4, 2/6, 2/8, 3/0

**Full Louver Bifold 6/7**  
2/0, 2/6, 3/0



732 Half Louver

**Half Louver 6/8**  
1/6, 1/8, 2/0, 2/4, 2/6, 2/8, 3/0

**Half Louver Bifold 6/7**  
2/0, 2/6, 3/0



KP44

**4-Panel 6/8**  
1/6, 1/8, 1/10, 2/0, 2/2, 2/4, 2/6, 2/8, 2/10, 3/0

**4-Panel Bifold 6/7**  
2/0, 2/6, 3/0



KP66

**6-Panel 6/8**  
1/6, 1/8, 1/10, 2/0, 2/2, 2/4, 2/6, 2/8, 2/10, 3/0

**6-Panel 8/0**  
1/6, 2/0, 2/4, 2/6, 2/8, 3/0

**6-Panel Bifold 6/7**  
2/0, 2/6, 3/0



**Door Specifications**

	CP44 & CP66 Doors & Bifolds	All Other Doors Shown
Top Rail	4 1/8"	4 1/8"
Lock Rail	6 3/4"	6 7/8"
Bottom Rail: Passage	8 3/4"	8 25/32"
Stiles: Passage 1'0" - 1'4" (Louver only)		2 1/8"
1'6" - 3'0"		4 1/8"
1'6" - 1'10"	2 3/4"	
2'0" - 3'0"	4 1/8"	
Bottom Rail: Bifold	7 1/16"	7 1/2"
Stiles: Bifolds	1 5/8"	1 3/4"
Panels	Double Hip Raised	
Ovolo Sticking: add to stile width	3/8"	1/2"
Louver Slats - Pine		5/16" x 1 1/2"